


Adjustable clevis hangers are recommended for suspension of plain or insulated stationary piping. These hangers comes with a feature to vertically adjust the level post installation. Comes with intermediate sizes to match the insulated OD of the piping.



Material : Steel

Finish : Electrogalvanised post manufacture.

Options : EPDM Lined (suffix 'R')

Hot Dip Galvanized finish (suffix 'HDG')

Stainless Steel construction (suffix 'SS')

Compliance : US Standards MSS-SP58 & 69 (Type 1)

Federal Specification : WW-H-171E & A-A-1192A (Type 1)

Electro-Galvanized: finish as per ASTM B633 SC3 BS1706 FE/ZN12.

Underwriter's Laboratories (UL)

UL Listed for sizes 1/2" to 8"

Apart from the models listed in the table below, a full range in intermediate sizes are available to match the effective ODs of G-Fix RSI. This will further enhance the quality of the installation. Custom designed extended riser clamps with 4 bolts design are also available on application.

SELECTION TABLE FOR G-FIX ADJUSTABLE CLEVIS HANGERS

Model	Steel Nominal		Material Dimension (mm)		Hanger Rod Size (D)	Cross Bolt Dia	Max Load (kg)
	In	mm	Height (A)	Top Hole Dia (S)			
GFCH (UL), 1/2" (22mm)	1/2"	15	68	11	M10	M8	350
GFCH (UL), 3/4" (27mm)	3/4"	20	72	11	M10	M8	350
GFCH (UL), 1" (34mm)	1"	25	76	11	M10	M8	350
GFCH (UL), 1 1/4" (42mm)	1 1/4"	32	87	11	M10	M8	350
GFCH (UL), 1 1/2" (48mm)	1 1/2"	40	97	11	M10	M8	350
GFCH (UL), 2" (60mm)	2"	50	114	11	M10	M8	350
GFCH (UL), 2 1/2" (73mm)	2 1/2"	65	142	13	M12	M10	780
GFCH (UL), 3" (89mm)	3"	80	165	13	M12	M10	780
GFCH (UL), 4" (114mm)	4"	100	202	13	M12	M10	780
GFCH (UL), 5" (141mm)	5"	125	236	13	M16	M12	1250
GFCH (UL), 6" (168mm)	6"	150	278	13	M16	M12	1250
GFCH (UL), 8" (219mm)	8"	200	338	13	M16	M12	2100
GFCH 10" (273mm)	10"	250	419	17	M16	M16	2100
GFCH 12" (323mm)	12"	300	490	21	M20	M20	2100
GFCH 14" (356mm)	14"	350	556	21	M20	M20	3800
GFCH 16" (406mm)	16"	400	610	25	M24	M20	3800
GFCH 18" (450mm)	18"	450	675	25	M24	M24	4000
GFCH 20" (508mm)	20"	500	715	32	M30	M24	4000
GFCH 24" (610mm)	24"	600	850	32	M30	M24	9400
GFCH 30" (762mm)	30"	750	995	32	M30	M24	9400

*** Product specifications are subject to change without prior notice.